

## PNEUMATIC ANCHOR MACHINE



### General

The Pneumatic Anchor Machine manufactured by Aardwolf Industries LLC features pneumatic grinders and a vacuum-powered base. It is used to cut T-slots in the back of vanity tops for the attachment of anchor bolts used in under-counter sink or architectural facing systems. Two separate vacuum zones on the base can be turned on or off, enabling the machine to be used near edges.

### Features

- Industrial quick-couplers for both air and water
- Combination port that allows vacuum to be applied with compressed air via the built-in venturi vacuum generator
- The grinders accept any T diamond bit with a 6mm shank
- Water hose with ball valve and quick-coupler can be quickly detached and used to spray work area
- Machine cuts in both push and pull directions
- Alignment indicators on machine base
- Machined, anodized aluminum components
- Moulded rubber vacuum base seal

**Note:** The Portable Water Supply Tank is sold upon request.

## Specifications

|  | <b>Metric<br/>(mm-kg)</b> | <b>Imperial<br/>(inch-lb)</b> |
|--|---------------------------|-------------------------------|
| Net weight   | 3                         | 6.6                           |
| Collet diameter                                    | 6                         | 0.2"                          |
| No load speed 25,000 RPM                           |                           |                               |
| Water connection hose thread- 1/4" PT              |                           |                               |
| Air connection 1/4" industrial series coupler plug |                           |                               |
| Vacuum base -80 kPa vacuum                         |                           |                               |